

	PELCO SPECTRA II	AMERICAN DYNAMICS DELTA DOME	PANASONIC WV-CS854	PHILLIPS / BURLE TC790	PHILLIPS LTC0809	KALATEL KTA-8CA CYBER DOME	SENSORMATIC SPEED DOME ULTRA
CONTROLLED BY COMPETITIVE SYSTEMS	YES	YES	YES	NO	NO	NO	NO
CONTROL INTERFACE PROTOCOL	RS-422	RS-422	RS-485	RS-232	RS-232	RS-422	RS-422
LIGHT SENSITIVITY (LUX)	1.5	1.5	1.0	2.0	5.0	3.0	2.25
BACKLIGHT COMPENSATION	NO	NO	YES	YES (OPTION)	YES (OPTION)	YES	YES
SIGNAL TO NOISE RATIO	46DB	48DB	50DB	46DB	44DB	46DB	48DB
OPTICAL ZOOM	16X	16X	22X	10X	16X	16X	12X
ELECTRICAL ZOOM	8X	8X	10X	N/A	6.25X	8X	4X
TOTAL ZOOM MAGNIFICATION	128X	128X	220X	10X	100X	128X	48X
BUILT IN MOTION DETECTOR	NO	NO	YES	NO	NO	NO	NO
PRIVACY ZONE VIDEO MASKING	YES (OPTION)	NO	YES	NO	NO	NO	NO
HORIZONTAL RESOLUTION (LINES)	450	450	480	440	425	450	450
CAMERA OPERATIONAL TEMPERATURE (WITHOUT HEATER/FAN)	0C TO 50C	-10C TO 50C	-10C TO 50C	-10C TO 50C	-10C TO 50C	-10C TO 50C	-10C TO 50C
ALARM INPUTS	7	1	4	N/A	N/A	N/A	4
ALARM OUTPUTS	2	4 (OPTION)	2	N/A	N/A	N/A	4
POWER INPUT	24VAC 30 WATTS	24VAC 16WATTS	24VAC 18W	VARIOUS 30WATTS	24VAC 15WATTS	24VAC 16WATTS	24VAC 16WATTS

[REDACTED]